# SUZUKI GSX-S1000/F(17-20) EEC SLIP-ON R-11Sq

Be sure to read the instruction carefully before starting the work. It is necessary to follow the contents to install Yoshimura product.

**CAUTION** Before beginning installation, let motorcycle cool down.

**CAUTION** Be sure not to damage each part during installation.

Torque specification must be followed. If neglected, it may cause bolt and nut to fall off and damage to Yoshimura product and motorcycle.

Metal Magic sleeve is coated with heat-resistant paint. Handle with care not to be hit or scratched by surroundings as the coating may come off. When cleaning silencer, use soft cloth with dish soap but do not use metal polish or chemical cleaner.

Titanium Blue sleeve is colored by anodizing. Handle with care as the color may change. When cleaning silencer, use soft cloth with dish soap but do not use metal polish or chemical cleaner.

#### 1. Product Information:

Description	SUZUKI GSX-S1000/F EEC Slip-On R-11Sq	Cyclone Type	S196S1QC1	
Part Number	Satin Finish Sleeve (SSF) : 1F0-196-L13G0	Main Material	Stainless steel	
	Metal Magic Sleeve (SM) : 1F0-196-L12G0	EEC Approval No.	e3 10004G	
	Titanium Blue Sleeve (STB) : 1F0-196-L16G0	Weight	(SSF) & (SM) : 3.2kg	
		[STD : 2.3kg]	(STB) : 3.0kg	

### 2. Applicable Model:

## 3. Optional Part:

Description	Part No.	
Silencer Bracket Set	194-196-0010	

## 4. Contents:

No.	Descriptions	Part No.	Q'ty	No.	Descriptions	Part No.	Q'ty
1	Tailpipe	115-196-L100	1	8	Washer M6x13	812-206-1310	2
2	Silencer Assy, (SSF)	1F6-196-L13G0	1	9	Grommet Rubber	553-565-0000	1
	Silencer Assy, (SM)	1F6-196-L12G0		10	Grommet Spacer	850-208-1212	1
	Silencer Assy, (STB)	1F6-196-L16G0		11	Flange Nut M6	823-006-1000	2
3	Silencer Bracket #1	161-196-0300	1	12	Flange Nut M8	823-008-1250	1
4	Silencer Bracket #2	161-196-0210	1	13	Exhaust Spring	118-001-0000	2
5	Cap Bolt M8x30	800-208-5030	3	14	Heat Guard	161-196-0000	1
6	Button Bolt M6x20	803-206-4020	2	15	Button Bolt M6x12	803-206-4012	1
7	Washer M8x26	812-108-2600	3	16	Conical Spring Washer M6	810-206-0000	1

